



## SK1050 ATTACHMENTS

The Ditch Witch® organization offers a full line of quick-change attachments compatible with the SK1050 Mini Skid Steer. Visit the SK1050 product page on [ditchwitch.com](http://ditchwitch.com) to use our interactive attachment selector, or ask your Ditch Witch dealer about additional attachment options.

# SK1050 MINI SKID STEER SPECIFICATIONS

	U.S.	METRIC
<b>DIMENSIONS (STD)</b>		
Operating height, max std. bucket (A)	105 in	2.67 m
Overall length of machine, std. bucket	105 in	2.67 m
Overall length of loader, no attachment (E)	86 in	2.19 m
Overall machine height (C)	57 in	1.45 m
Machine weight (no attachment, fluids full)	3,435 lb	1558 kg
Operating capacity		
35% tipping capacity	1,062 lb	482 kg
Tipping capacity	3,035 lb	1377 kg
Hinge pin height, max (B)	83 in	2.10 m
Wheelbase/track length (F)	43 in	1.09 m
Track width, max (O)	42 in	1.06 m
Ground clearance, min (I)		
Center	7.4 in	188 mm
Side	3.7 in	94 mm
Angle of departure (J)	27°	

<b>POWER</b>		
Engine	Yanmar® 3TNV88C	
Fuel	Diesel	
Gross power rating	37 hp	27.6 kW
Emissions compliance	EPA Tier 4	EU Stage IIIA
Number of cylinders	3	
Displacement	100.1 in <sup>3</sup>	1.64 L
Bore	3.46 in	88 mm
Stroke	3.54 in	90 mm
Rated speed	3,000 rpm	

<b>OPERATION</b>		
Ground drive speed		
Forward/reverse	4.7 mph	7.6 km/h
Ground pressure (ISO/CD 16754)		
9-in (230-mm) tracks	4.9 psi	0.34 bar

	U.S.	METRIC
<b>HYDRAULIC SYSTEM</b>		
Auxiliary circuit		
Double gear pump		
Pressure	3,625 psi	250 bar
Flow rate	13.9 gpm	52.6 l/min
<b>FLUID CAPACITIES</b>		
Fuel tank capacity	10.5 gal	40 L
Engine oil, w/filter	5 qt	4.7 L
Hydraulic reservoir capacity	9.2 gal	35 L
<b>BATTERY</b>		
SAE reserve capacity rating	110 min	
SAE cold crank @ 0°F (-18°C)	800 amps	
Electrical system	12V	

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.

