

OPERATING PERFORMANCE

Operating Weight - Canopy	7,485 lb
Operating Weight - Cab	7,780 lb
Tipping Load	5,269 lb
Rated Operating Capacity, SAE J818*	1,841 lb
Operating Load at 50% of Tipping Load	2,635 lb
Bucket Breakout Force	5,930 lb
Lift Arm Breakout Force	4,860 lb
Traction Force	8,655 lb
Ground Pressure - 12.6" Track	5.1 psi
Travel Speed -	Low 4.3 mph
Travel Speed -	High 6.2 mph

*Rated operating capacity of track loaders is rated according to SAE J818 at no more than 35% of the tipping load.

HYDRAULIC SYSTEM

Auxiliary Flow - Primary Circuit	17.8 gpm
Hydraulic System Pressure	2,988 psi

ENGINE

Make / Model	Kubota / V2403-CR-TE4B
Engine Displacement	148.5 cu in
Horsepower @ 2,700 rpm	65.2 hp
Maximum Torque @ 1,500 rpm	144.3 ft-lb

FLUID CAPACITIES

Engine Lubrication	7.6 qt
Cooling System	14.0 qt
Fuel Tank Capacity	20.0 gal
Fuel Consumption (65% of Full Load)	2.69 gal/hr
Hydraulic Reservoir Capacity	7.9 gal(51.0 L)