DINGO TX 1000



UNMATCHED STRENGTHOver 1,000-lb rated operating capacity to lift and transport heavy loads.



		DINGO TX 1000 (MODEL 22327)	DINGO TX 1000 WIDE TRACK (MODEL 22328)	
ENGINE	Engine	Kubota® D1305 Diesel		
	Air Filter	Two-stage, heavy-duty, remote		
Cooling System		Liquid Cooled		
	Fuel Tank	11.5 gallons	11.5 gallons (44 liters)	
	Oil Capacity	6.0 quarts (6.0 quarts (5.7 liters)	
HYDRAULIC SYSTEM	Hydraulic Pressure	3,000 PSI		
	Hydraulic Flow		Traction: 13.3 gpm (each pump) Auxiliary: 15.2 gpm	
	Reservior Capacity	15.2 gallons (57.5 liters)		
TRACKS	Standard	Sprocket-drive, 6 road wheels per side		
	Traction	Dual hydrostatic pump		
DIMENSIONS	Track Width	127.6" x 5.9" (324 cm x 15 cm)	127.6" x 9.5" (324 cm x 24 cm)	
	Wheelbase	41" (10) cm)	
Ground Clearance		6.0" (15 cm)		
Overall Dimensions (WxLxH) With Bucket		33.7" x 100.7" x 53.2" (86 x 256 x 135 cm)	41" x 100.7" x 53.2" (104 x 256 x 135 cm)	
Overall	Dimensions (WxLxH) Without Bucket	33.7" x 81.7" x 53.2" (86 x 208 x 135 cm)	41" x 81.7" x 53.2" (104 x 208 x 135 cm)	
Maximum Operating Height		105" (267 cm)		
Hinge Pin Height		81" (206 cm)		
Dump Height		61" (155 cm)		
Dump Angle		40-degrees		
Reach - Fully Raised		24.5" (62 cm)		
Ground Speed		4.7 mph (7.6 km/h)		
Weight		2610 lbs (1184 kg)	2790 lbs (1266 kg)	
Tip Capacity		2,857 lbs (1,296 kg)	3,071 lbs (1,393 kg)	
Rated Operating Capacity (35% of Tip Capacity)*		1,000 lbs (454 kg)	1,075 lbs (488 kg)	
Ground Pressure		5.5 PSI	3.6 PSI	



MAXIMUM HEIGHT & REACH 81" hinge pin height allows operator to dump into 30-yard dumpster or side of one-ton truck.



TORO EXCLUSIVE CONTROLSEffortless traction controls are easy to use for all-day productivity.



